

EV-FLEETTM

Electric Vehicle Level 2 Charging Station

Meet the best-in-class EV charging network technology for fleet vehicle charging. The EV-FLEET™ Level 2 charging station is the ideal EV charging solution for medium to heavy duty applications.

- + Up to 2.5x faster than standard level 2 chargers
- + Sleek, compact modern design
- + Flexibly mounted on a wall, ceiling, pole or pedestal
- + WiFi & LTE cellular enabled for public or private networks
- + RFID, Smartphone App and Bluetooth user authentication
- + Real-time load management and demand response
- + Tamper resistant; rated for indoor/outdoor use
- + Universal compatibility





EV-FLEET™ Specifications

Electrical	+ 80 A/ 19.2 kW max output. 60 Hz	
	+ 208/240 VAC. single phase input	
	+ Hardwired, single port	
Connector	+ 25 ft. charging cable	
	+ SAE J1772 Type 1 standard compliant	
Network Connectivity	+ Built-in Wi-Fi (802.11 b/g/n)	
	+ Built-in LTE Cellular	
***************************************	+ OCPP 1.6 Communication Protocol	
Firmware	+ 90-day, 15-minute encrypted interval data storage	
	+ Persistent data storage upon power interruption	
	+ Over the Air (OTA) updates available via Loop Network $^{\!\top\!$	
0	Neeth arranged at at timbs NEMA 2D (IDEE) IMAG tarrang against	
Core Specifications	+ Weatherproof.dust-tight: NEMA 3R (IP55). IK10 tamper resistant	
	+ Integrated cable management saddle and holster	
	+ Operating Temperature= -35 to 55 °C / -31 to 131 °F	
	+ Metering Accuracy= Embedded+/- 1%	
	+ User Interface= Configurable OLED display	
	+ Status Indicators= Power/Ready, Charging. Fault	
	+ Wall, ceiling, pole or pedestal mounting options	
	+ Main Enclosure Dimensions= 14.07" H x 10.63" W x 5.11" D	
	+ Weight: 30lbs	
	LUI 4000/2074/2504 FOO Dowl 45D	
Certifications & Standards	+ UL 1998/2231/2594, FCC Part 15B,	
	+ Open ADR 2.0b compliant	
Loop Network™ App	+ Web-based portal for desktop access & remote troubleshooting	
(Optional)	+ Public or private network enabled	
	+ User access control through RFID, NFC, Bluetooth and/or QR code	
	+ Flexible billing models (Pay-Per-Use vs. Subscription)	
	+ Automated billing & real-time payment resolution	
Warranty	+ 3-year limited product warranty (parts only); optional	
	5-year and 10-year extended warranties available	
	+ Wall Mount. Single Port Charger #EVS-80A-L2-001	
	+ Pedestal Mount. Single Port Charger #EVS-80A-L2-001-1P	
	+ Pedestal Mount. Dual Single Port Chargers #EVS-80A-L2-001-2P	

Power Settings

Current (A)	kW	OCPD Size
40	9.6	50
48	11.5	60
55	13.2	70
64	15.4	80
70	16.8	90
80	19.2	100

Dimensions

